COMPETITION: LOCATION: TEAM: MAKE MODEL CODE INSPECTED TEST P = PASS P - PASS F - FAIL PRESSURE* F = FAIL		BAT CONTROL LIST					
TEAM: MAKE MODELCODE INSPECTED TEST P = PASS P = PAIL P = PAI						softball'''	
MAKE MODEL CODE INSPECTED TEST P = PASS P =		LOCATION:				europe	
P-PASS F-FAIL PRESSURE* F = FAIL					e e e e e e e e e e e e e e e e e e e		
1	BAT#	MAKE	MODEL CODE				
3 4 6 6 6 6 6 6 7 7 7 8 8 8 8 9 9 9 9 9 9 9 9 9 9 9 9 9	1			T TASS T TAIL	T NESSONE	TETALE	
4	2						
5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	3						
6	4						
7 8 9 10 11 12 13 14 15 16 17 18 19 20 TOTALS:	5						
8 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	6						
9	7						
10	8						
11 12 13 3 14 4 15 4 16 4 17 4 18 4 19 4 20 5 TOTALS: 1	9						
12	10						
13	11						
14	12						
15	13						
16	14						
17	15						
18	16						
19	17						
20 TOTALS:	18						
TOTALS:	19						
	20						
Date would make an accordable accommunical level and for that moutivelends was of hot. The accommunical							

Bats must meet or exceed the compression level set for that particular type of bat. The compression benchmark for approved bats is 1460 PSI, unless the bat is of non-linear construction in which case the compression shall be the benchmark established for that make and model of bat